

Spacek et al., 2021, Figure 2

Figure 2e

(I) Fit intercept-only model to slope (all spikes)

```
# Random intercept for neurons,
# random intercept for experiments, nested in series
lmer.2e_slope = lmer(slope ~ 1 + (1 | uid) + (1 | sid/eid),
                      data = tb_all %>% drop_na(slope))

display(lmer.2e_slope)

## lmer(formula = slope ~ 1 + (1 | uid) + (1 | sid/eid), data = tb_all %>%
##       drop_na(slope))
##   coef.est  coef.se
##   0.75     0.05
##
## Error terms:
##   Groups    Name        Std.Dev.
##   uid      (Intercept) 0.22
##   eid:sid (Intercept) 0.07
##   sid      (Intercept) 0.12
##   Residual           0.17
##   ---
##   number of obs: 119, groups: uid, 63; eid:sid, 24; sid, 11
##   AIC = 31.7, DIC = 13.5
##   deviance = 17.6
```

95-% confidence interval on slope

0.75 ± 0.10

n = 63 neurons from 6 mice

(II) Fit intercept-only model to threshold (all spikes)

```
# Random intercept for neurons,  
# random intercept for experiments, nested in mice  
lmer.2e_thresh = lmer(thresh ~ 1 + (1 | uid) + (1 | mid/eid),  
                      data = tb_all %>% drop_na(thresh))  
  
display(lmer.2e_thresh)  
  
## lmer(formula = thresh ~ 1 + (1 | uid) + (1 | mid/eid), data = tb_all %>%  
##       drop_na(thresh))  
##   coef.est  coef.se  
##     -0.19      0.58  
##  
## Error terms:  
##   Groups    Name        Std.Dev.  
##   uid       (Intercept) 1.73  
##   eid:mid  (Intercept) 1.45  
##   mid       (Intercept) 0.58  
##   Residual            3.55  
## ---  
## number of obs: 119, groups: uid, 63; eid:mid, 24; mid, 6  
## AIC = 683.4, DIC = 674.7  
## deviance = 674.0
```

95-% confidence interval on threshold

-0.19 ± 1.15

n = 63 neurons from 6 mice

Figure 2f

Goodness-of-fit vs burst ratio during suppression

```
# Random intercept for neurons,
# random intercept for experiments, nested in series
lmer.2f = lmer(rsq ~ suppression_meanburstratio + (1 | uid) + (1 | sid/eid),
               data = tb_all %>% drop_na(rsq, suppression_meanburstratio))

display(lmer.2f)

## lmer(formula = rsq ~ suppression_meanburstratio + (1 | uid) +
##       (1 | sid/eid), data = tb_all %>% drop_na(rsq, suppression_meanburstratio))
##             coef.est    coef.se
## (Intercept)      0.70     0.05
## suppression_meanburstratio -1.29     0.25
##
## Error terms:
## Groups   Name        Std.Dev.
## uid      (Intercept) 0.16
## eid:sid (Intercept) 0.10
## sid      (Intercept) 0.11
## Residual           0.11
## ---
## number of obs: 119, groups: uid, 63; eid:sid, 24; sid, 11
## AIC = -40, DIC = -62.5
## deviance = -57.3
anova(lmer.2f)

## Type III Analysis of Variance Table with Satterthwaite's method
##              Sum Sq Mean Sq NumDF DenDF F value    Pr(>F)
## suppression_meanburstratio 0.33449 0.33449     1  67.792 26.913 2.099e-06 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

95-% confidence interval on slope

-1.29 ± 0.50

n = 63 neurons from 6 mice

Figure 2g

Goodness-of-fit with and without removal of burst spikes

```
# Random intercept for neurons,
# random intercept for experiments, nested in series
lmer.2g = lmer(rsq ~ allSpikes + (1 | uid) + (1 | sid/eid),
               data = tb %>% drop_na(rsq, allSpikes))

display(lmer.2g)

## lmer(formula = rsq ~ allSpikes + (1 | uid) + (1 | sid/eid), data = tb %>%
##       drop_na(rsq, allSpikes))
##           coef.est  coef.se
## (Intercept)  0.61      0.06
## allSpikes   -0.03      0.01
##
## Error terms:
## Groups     Name        Std.Dev.
## uid        (Intercept) 0.21
## eid:sid    (Intercept) 0.12
## sid        (Intercept) 0.13
## Residual          0.09
## ---
## number of obs: 238, groups: uid, 63; eid:sid, 24; sid, 11
## AIC = -214, DIC = -248.1
## deviance = -237.0
anova(lmer.2g)

## Type III Analysis of Variance Table with Satterthwaite's method
##           Sum Sq Mean Sq NumDF DenDF F value Pr(>F)
## allSpikes 0.03919 0.03919     1 160.8  4.8086 0.02975 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Predicted average effect

All spikes: $R^2 = 0.58$
non-burst spikes: $R^2 = 0.61$
 $n = 63$ neurons from 6 mice

Figure 2h

Goodness of fit with and without removal of tonic spikes

```
# Random intercept for neurons,
# random intercept for experiments, nested in series
lmer.2h = lmer(rsq ~ allSpikes + (1 | uid) + (1 | sid/eid),
               data = tb %>% drop_na(rsq, allSpikes))

display(lmer.2h)

## lmer(formula = rsq ~ allSpikes + (1 | uid) + (1 | sid/eid), data = tb %>%
##       drop_na(rsq, allSpikes))
##           coef.est  coef.se
## (Intercept) 0.58      0.06
## allSpikes   0.00      0.01
##
## Error terms:
## Groups     Name        Std.Dev.
## uid        (Intercept) 0.22
## eid:sid    (Intercept) 0.11
## sid        (Intercept) 0.14
## Residual          0.08
## ---
## number of obs: 239, groups: uid, 63; eid:sid, 24; sid, 11
## AIC = -232.7, DIC = -266.8
## deviance = -255.8
anova(lmer.2h)

## Type III Analysis of Variance Table with Satterthwaite's method
##             Sum Sq   Mean Sq NumDF DenDF F value Pr(>F)
## allSpikes 3.8886e-05 3.8886e-05      1 161.96 0.0054 0.9415
```

Predicted average effect

All spikes: $R^2 = 0.58$
Randomly removed spikes: $R^2 = 0.58$
 $n = 63$ neurons from 6 mice

Figure 2i

(I) Fit intercept-only model to slope (non-burst spikes)

```
# Random intercept for neurons,
# random intercepts for experiments, nested in series
lmer.2i_slope = lmer(slope ~ 1 + (1 | uid) + (1 | sid/eid),
                      data = tb_nonburst %>% drop_na(slope))

display(lmer.2i_slope)

## lmer(formula = slope ~ 1 + (1 | uid) + (1 | sid/eid), data = tb_nonburst %>%
##       drop_na(slope))
##   coef.est  coef.se
##   0.74      0.04
##
## Error terms:
##   Groups     Name        Std.Dev.
##   uid        (Intercept) 0.26
##   eid:sid   (Intercept) 0.09
##   sid        (Intercept) 0.02
##   Residual             0.15
##   ---
##   number of obs: 119, groups: uid, 63; eid:sid, 24; sid, 11
##   AIC = 32.3, DIC = 13.4
##   deviance = 17.9
```

95-% confidence interval

Intercept of 0.74 ± 0.09
n = 63 neurons from 6 mice

(II) Fit intercept-only model to threshold (non-burst spikes)

```
# Random intercept for neurons,
# random intercept for experiments, nested in series, nested in mice
lmer.2i_thresh = lmer(thresh ~ 1 + (1 | uid) + (1 | mid/sid/eid),
                      data = tb_nonburst %>% drop_na(thresh))

## boundary (singular) fit: see ?isSingular
## Warning: Model failed to converge with 1 negative eigenvalue: -1.2e+00
display(lmer.2i_thresh)

## lmer(formula = thresh ~ 1 + (1 | uid) + (1 | mid/sid/eid), data = tb_nonburst %>%
##       drop_na(thresh))
##   coef.est  coef.se
##   0.09      0.63
##
## Error terms:
##   Groups        Name        Std.Dev.
##   uid          (Intercept) 1.83
##   eid:(sid:mid) (Intercept) 1.64
##   sid:mid      (Intercept) 1.04
##   mid          (Intercept) 0.00
##   Residual            3.26
##   ---
##   number of obs: 119, groups: uid, 63; eid:(sid:mid), 24; sid:mid, 11; mid, 6
##   AIC = 676.2, DIC = 666
##   deviance = 665.1
```

95-% confidence interval

Intercept of 0.09 ± 1.3

Fit a single model to Figures 2e and 2i

(I) Predict slope based on firing mode (all spikes vs non-burst spikes)

```
# Random intercept for neurons,
# random intercept for experiments, nested in series, nested in mice
lmer.2ei_slope = lmer(slope ~ allSpikes + (1 | uid) + (1 | mid/sid/eid),
                      data = tb %>% drop_na(slope, allSpikes))

display(lmer.2ei_slope)

## lmer(formula = slope ~ allSpikes + (1 | uid) + (1 | mid/sid/eid),
##       data = tb %>% drop_na(slope, allSpikes))
##   coef.est  coef.se
## (Intercept) 0.73     0.05
## allSpikes    0.01     0.02
##
## Error terms:
##   Groups        Name        Std.Dev.
##   uid          (Intercept) 0.26
##   eid:(sid:mid) (Intercept) 0.09
##   sid:mid      (Intercept) 0.08
##   mid          (Intercept) 0.00
##   Residual            0.13
## ---
## number of obs: 238, groups: uid, 63; eid:(sid:mid), 24; sid:mid, 11; mid, 6
## AIC = -81, DIC = -116.3
## deviance = -105.7

anova(lmer.2ei_slope)

## Type III Analysis of Variance Table with Satterthwaite's method
##           Sum Sq  Mean Sq NumDF DenDF F value Pr(>F)
## allSpikes 0.010024 0.010024     1 162.65  0.6033 0.4385
```

(II) Predict threshold based on firing mode (all spikes vs non-burst spikes)

```
# Random intercept for neurons,
# random intercept for experiments, nested in series, nested in mice
lmer.2ei_thresh = lmer(thresh ~ allSpikes + (1 | uid) + (1 | mid/sid/eid),
                       data = tb %>% drop_na(thresh, allSpikes))

display(lmer.2ei_thresh)

## lmer(formula = thresh ~ allSpikes + (1 | uid) + (1 | mid/sid/eid),
##       data = tb %>% drop_na(thresh, allSpikes))
##           coef.est coef.se
## (Intercept) -0.04      0.71
## allSpikes    -0.15      0.33
##
## Error terms:
##   Groups        Name        Std.Dev.
##   uid          (Intercept) 3.02
##   eid:(sid:mid) (Intercept) 1.62
##   sid:mid      (Intercept) 1.17
##   mid          (Intercept) 0.34
##   Residual            2.58
##   ---
## number of obs: 238, groups: uid, 63; eid:(sid:mid), 24; sid:mid, 11; mid, 6
## AIC = 1274.8, DIC = 1262.1
## deviance = 1261.4
anova(lmer.2ei_thresh)

## Type III Analysis of Variance Table with Satterthwaite's method
##           Sum Sq Mean Sq NumDF DenDF F value Pr(>F)
## allSpikes 1.3153 1.3153     1 157.31 0.1976 0.6572
```